



29

ALTERNATIVE100 dB

| | | | |
|---|---|--|---|
| CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR | Tufted 1/10" Loop Tip Sheared Tufté 1/10" Bouclé Tip Sheared Getuftet 1/10" Schlinge Tip Sheared Getuft 1/10" Loop Tip Sheared | FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG | EN 13501-1 B _s -s1 |
| PILE MATERIAL COUCHE D'USURE POLMATERIAL POOLMATERIAAL | 100% ECONYL® yarn 100% Regenerated Space Dyed Nylon | FASTNESS TO LIGHT SOLIDITÉ À LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID | ISO 105-B02 ≥ 7 |
| SECONDARY BACKING DOSSIER RÜCKENAUSSTATTUNG RUG | dBack: modified bitumen enhanced with a thermoplastic elastomer, covered with a sound absorbing, recycled polyester felt. | RUBBING FASTNESS SOLIDITÉ AU FROTTEMENT REIBECHTHEIT WRIJFECHTHEID | EN ISO 105-X12 ≥ 4 |
| TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT | Ca. 5200 g/m ² | COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID | EN ISO 105-E01 ≥ 4 |
| PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT | Ca. 800 g/m ² | THERMAL RESISTANCE RÉSISTANCE THERMIQUE WARMEDURCHLABWIDERSTAND WARMTEDOORLAATWEERSTAND | ISO 8302 ≤ 0,17 m ² K/W |
| PILE ABOVE BACKING POIDS DE VELOURS UTILE POLNUTZSCHICHTGEWICHT NUTTIG POOLGEWICHT | Ca. 460 g/m ² | IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNGMAß GELUIDSISOLATIE | ISO 10140 ΔL: 42 (1000 Hz) |
| TOTAL HEIGHT EPAISSEUR TOTALE GESAMTDICKE TOTAAL DIKTE | Ca. 9,3 mm | SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE | ISO 354 α _v : 0,30 |
| PILE HEIGHT EPAISSEUR DU VELOURS POLDICKE POOLHOOGTE | Ca. 3,4 mm | PERMANENT ANTISTATIC ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH PERMANENT ANTISTATISCH | ISO 6356 ≤ 2 kV |
| PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTE POOLDICHTHEID | Ca. 0,135 g/cm ³ | TRANSVERSAL RESISTANCE RÉSISTANCE TRANSVERSALE DURCHGANGSWIDERSTAND DOORGANGSWEERSTAND | ISO/DIS 10965 ≤ 10 ¹¹ Ohm |
| TUFT DENSITY NOMBRE DE TOUFFES NOPPENZAHL AANTAL PUNTEN | Ca. 206.000 /m ² | SIZE & PACKING DIMENSION & EMBALLAGE ABMESSUNG & VERPACKUNG AFMETINGEN & VERPAKKING | 50 cm x 50 cm box: 4 m ² pallet: 20 boxes |
| CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE | EN 1307 33 - LC2 | NUMBER OF COLOURS NOMBRE DE COLORIS ANZAHL DER FARBEN AANTAL KLEUREN | 11 |
| CASTOR CHAIR SUITABILITY EMPLOI CHAISE À ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID | EN 985 A : continuous use | DIMENSIONAL STABILITY STABILITÉ DIMENSIONNELLE DIMENSIONSTABILITÄT DIMENSIONELE STABILITEIT | EN 986 max. 0,2% |
| DONNÉES ENVIRONNEMENTALES | Démarche HQE® : cf. FDES suivant NF P01-010 Déclaration du 30/07/2003 | GUT-NR | F5450983 |
| | | LEED® | Product contributes toward satisfying Credit 4.3 under LEED®. Products are not reviewed under LEED®, LEED® credit requirements cover the performance of materials in aggregate, not the performance of individual products of brands. |



modulyss®
Zevensterrestraat 21
B 9240 Zele
T +32 (0)52 80 80 80
F +32 (0)52 80 82 00
info@modulyss.com
www.modulyss.com